

Atlanta Attachment



Specifications	Model: 5504-J-34
MAX. Sewing Speed	6,000 rpm
Stitch Length	2.5 to 5mm
Needle Bar Stroke	28.8mm
Presser Footlift	8mm
Needle Size	DO x 5
Needle Gauge	N/A
Overedging Width	4.8mm
Bottom Differential Feed Ratio	For gathering 1:1.75 (max. 1:3.8)
Top Feed Vertical Stroke	N/A
Top Feed Longitudinal Stroke	N/A
Lubrication	Automatic
Stitch Type	301



Model 5504-J-34

Specially Modified, 1-Needle 3-Thread Overedge (504 stitch), Variable Top-feed, Bottom Differential Feed

- Modified top feed mechanism to increase walking movement of top feed
- Upper and Lower needle bar bushings
- Automatic Lubrication
- Cartridge type oil filter and cooling fan
- Push button stitch length adjustment
- Variable top feed adjusted by lever with micro adjustment
- Bottom differential feed adjusted by lever with micro adjustment
- Thread & needle lubrication system
- High lift stepping foot (foot lifts during feed stroke)

Optional:

- Pneumatic foot lifter
- Vacuum chain cutter
- Gathering attachments



Website: www.atlatt.com email: sales@atlatt.com

This equipment is protected by one or more of the following patents:
US patents: 4,280,421; 4,432,294; 4,466,367; 4,644,883; 5,134,947; 5,159,889; 5,203,270; 5,522,332; 5,524,563; 5,562,060; 5,634,418; 5,647,293;
5,657,711; 5,743,202; 5,865,135; 5,899,159; 5,915,319; 5,918,560; 5,979,345; 6,035,794; 6,055,921; 6,202,579; 6,279,869; 6,295,481; 6,494,255;
6,802,271; 6,574,815 B2; 6,834,603 B1; 6,968,794 B1
Foreign patents: 9-520,472; 0,537,323; 92,905,522.6; 96,936,922.2; 2,076,379; 2,084,055.
Other U.S. and Foreign Patents Pending. Copyright 2006 Atlanta Attachment Co.

05087011506

The **Sudden Service**™ Company

Atlanta Attachment Company
362 Industrial Park Drive
Lawrenceville, GA 30045
(770) 963-7369 • FAX (770) 963-7641

