



Specifications	Model: 1591 BLN 5
MAX. Sewing Speed	3,500 spm
Stitch Length	0.8 to 5.0 mm
Needle Bar Stroke	N/A
Presser Footlift	10 mm
Needle Size	134LLCR to size 100
Rotating Hook	Standard capacity, bobbin case, vertical axis
Alternating Foot Stroke	N/A
Needle Gauge	N/A
Hook Safety Clutch	Standard
Lubrication	Automatic
Working Space	260 mm arm to needle
Stitch Type	301



Model 1591 BLN 5

Postbed, Needle-feed, Wheel-Feed, Driven Roller Presser, Lockstitch, Automatic Underbed Thread Trimmer, Automatic Footlift, Automatic Backtack.

- Built-in integrated motor and control panel
- Bottom wheel feed and roller presser are driven by separate stepping motors and can be set individually
- Stitch length adjusted via control panel
- Automatic hook oiling
- Standard hook and bobbin case for maximum stitch quality
- No air required, functions are controlled electronically
- Hook safety clutch

Optional:

- Edge Trimmer separately driven from bottom (-725/04) or top (-726/05)
- Trim Margins 0.8, 1.0, and 1.2mm
- Edge guides
- Material guides



Website: www.atlatt.com email: sales@atlatt.com

This equipment is protected by one or more of the following patents:
US patents: 4,280,421; 4,432,294; 4,466,367; 4,644,883; 5,134,947; 5,159,889; 5,203,270; 5,522,332; 5,524,563; 5,562,060; 5,634,418; 5,647,293;
5,657,711; 5,743,202; 5,865,135; 5,899,159; 5,915,319; 5,918,560; 5,979,345; 6,035,794; 6,055,921; 6,202,579; 6,279,869; 6,295,481; 6,494,255;
6,802,271; 6,574,815 B2; 6,834,603 B1; 6,968,794 B1
Foreign patents: 9-520,472; 0,537,323; 92,905,522.6; 96,936,922.2; 2,076,379; 2,084,055.
Other U.S. and Foreign Patents Pending. Copyright 2006 Atlanta Attachment Co.

05087011506

The **Sudden Service**™ Company

Atlanta Attachment Company
362 Industrial Park Drive
Lawrenceville, GA 30045
(770) 963-7369 • FAX (770) 963-7641

