

Panel - Serging & Flanging

Tapas - Sobrehilar y Aplicar Rebordes

New!

Images may include options. Las imágenes pueden incluir opciones.



1317C Semi-Automatic Panel Serging and Flanging with Belted Conveyor

- Powered conveyor table
- Corner turning arm with adjustable radius
- Automatic flange cutting and re-insert
- Auto stop at corners
- Auto unload feature
- Electronic thread break detection
- Reliable Serial Bus Control System
- Heavy-duty High-Lift five-thread safety stitch sewing head
- Electronic puller

Sobrehilado y Aplicación de Reborde Semi Automático con Cinta Transportadora

- *Mesa transportadora motorizada*
- *Brazo giratorio de esquinas con radio ajustable.*
- *Corte y re inserción de reborde automático*
- *Parada automática en las esquinas*
- *Función de descarga automática*
- *Detección electrónica de rotura de hilo.*
- *Sistema de control Serial Bus confiable*
- *Cabezal de Costura con puntada de seguridad de alta resistencia de cinco hilos y alta elevación de prénsatelas.*
- *Arrastrador electrónico*



Technical Information

CLASS

- **11317C** Semi-Automatic panel serging and flanging with belted conveyor


Información Técnica

CLASES

- **11317C** Sobrehilado y Aplicación de Reborde Semi Automático con Cinta Transportadora



SPECIFICATIONS / ESPECIFICACIONES		
Max sewing speed (rpm) / Max velocidad de costura (rpm)	3500	
Factory preset speed (rpm) / Velocidad de fábrica (rpm)	3500	
Max stitch length (spi) / Max longitud de puntada (spi)	4	
Needle distance (inch) / Distancia entre agujas (pulgadas)	1/4 - 3/4	
Needle system / Sistema de aguja	SBN149x7#140	
Needle size / Tamaño de aguja	140	
Weight of material / Tipo de material	MEDIUM / HEAVY	
Voltage (v/ph/hz) / Voltaje (v/ph/hz)	220V 1PH 50/60HZ	
Current (amps) / Amperaje (amperios)	15	
Motor type / Tipo de motor	EFKA DC	
Air pressure (psi) / Presión de aire (psi)	80	
Air consumption (cfm) / Consumo de aire (cfm)	20	
Shipping weight (lbs) / Peso de embarque (lbs)	2500	1000
Shipping dimensions (w/l/h, inch) / Dimensiones de embarque (w/l/h, pulgadas)	192 x 91 x 45	72 x 65 x 72
PRODUCTION / PRODUCCIÓN		
Panels per hour / Tapas por hora	60	



Footprint
Vista Superior



www.atlatt.com • sales@atlatt.com
+1 (770) 963-7369 • FAX +1 (770) 963-7641
 362 Industrial Park Drive • Lawrenceville, GA 30046

PATENTS: Our equipment may be covered by one or more patents. Please go to the following web page for an up-to-date patent list: www.atlatt.com/patents © 2019 Atlanta Attachment Co. 18158030619



Atlanta Attachment Company
Sudden Service®