## **Flatbed Lockstitch**

## Single and Double Needle Flatbed **Lockstitch Compound Feed Machine**

- Automatic Lubrication System
- Second Stitch Length
- Automatic Presser foot Lift with Button for fast access for machine function
- Automatic thread trimmer, presser foot lift, and backtack



### **Technical Information**

| SPECIFICATIONS           | 1380TW1898D2T3      | 1380TW2898D2T3 |
|--------------------------|---------------------|----------------|
| Needles                  | Single              | Double         |
| Bobbin (mm)              | 28                  | 28             |
| Max sewing speed (rpm)   | 3500                | 2500           |
| Max Stitch Length (mm)   | 9                   |                |
| Presser Foot Height (mm) | 9                   |                |
| Needle System            | 135x17 size 120-160 |                |
| Thread                   | 20/3                |                |
| Clearance Under Arm (mm) | 300x120             |                |



### Options


HSM

Manual Suspended Edge Guide

-

**Custom Feed Components** 

## www.atlatt.com • sales@atlatt.com



362 Industrial Park Drive Lawrenceville, GA 30046 +1 (770) 963-7369



### **Atlanta Attachment Company** a Division of



# **1380TW** series

TYPICAL



TYPICAL

SPECIFICATIONS

Presser Foot Height (mm)

Clearance Under Arm (mm)

Needles

Bobbin (mm)

Needle System


## **Direct Drive Single** and Double Needle **Flatbed Lockstitch Compound Feed Machine**

- Clearance Under the Arm 355mm x 120mm
- Automatic Lubrication System
- Second Stitch Length
- Automatic Presser foot Lift with Button for fast access for machine function
- Automatic thread trimmer, presser foot lift, and backtack
- Electronic Hand wheel










362 Industrial Park Drive Lawrenceville, GA 30046 +1 (770) 963-7369







#### Options

a Division of

HSM

- Manual Suspended Edge Guide
- **Custom Feed Components**

**Atlanta Attachment Company** 

