Images may include options



## **Single and Double Needle Postbed** Lockstitch **Compound Feed Machine**

- Use of state of the art electronic control making all machine settings programmable into memory and thus recallable. This allows the process parameters to be free from operators influence and identical every time the program is recalled
- All machine settings are programmable and storable: stitch length, sewing feet pressure, top feed stroke, needle thread tension, clearance under the sewing feet
- Program chain function to combine different production steps directly on one machine
- Permanent measurement of material thickness resulting automatic changes to sewing feet pressure, sewing speeds, stitch length and thread tension corrections
- Integrated, electric bobbin winder (continuous winding process even when machine is stopped).
- Direct Drive Motor 750W
- User Identification by USB Dongle
- Tilt Assistant for easy cleaning and maintenance
- Electronic Hand Wheel
- Programmable fast access function button at needle area
- No Compress Air unless Options add that require air

## **Options**

- Manual Suspended Edge Guide
- Electronic Edge Guide (one or two Axis)
- Electronic Safety right hand slide plate
- Electronic Safety eye shield
- Bar Code Scanner for Program changes
- **Custom Feed Components**



## **Technical Information**

SPECIFICATIONS	1380V5300	1380V5320	1380V5340
Needles	Single	Double	Single
Bobbin	26mm		
Max Sewing Speed (RPM)	2500		
Post Position	Right	Double	Left
Max Stitch Length (mm)	12		
Presser Foot Height (mm)	20		
Presser Foot Stroke (mm)	9		
Needle System	134-35 size 90-180		
Thread	10/3		
Clearance Under Arm (mm)	350x310		





www.atlatt.com • sales@atlatt.com





