



- ▲ MUST REMOVE COVER AND SET SLIDE SWITCHES TO DESIGNATED CONFIGURATION
- ▲ MUST SET ADJUSTMENT SCREW TO 1 SECOND
- ▲ BACK OF 1550 I/O PLUG



NOTES: ALL WIRE 18AWG 300V UNLESS NOTED

THE INFORMATION ON THIS DRAWING IS THE INTELLECTUAL PROPERTY OF ATLANTA ATTACHMENT COMPANY AND ITS AFFILIATES. THIS DRAWING MAY NOT BE COPIED IN ANY FORM WHATSOEVER. THIS INFORMATION MAY NOT BE USED BY ANY UNAUTHORIZED PERSON OR COMPANY. IN ADDITION TO ANY CONFIDENTIALITY AND NON-DISCLOSURE OBLIGATIONS THAT CURRENTLY EXIST BETWEEN YOU AND ATLANTA ATTACHMENT COMPANY, YOUR USE OF THESE MATERIALS SERVES AS AN ACKNOWLEDGMENT OF THE CONFIDENTIAL AND PROPRIETARY NATURE OF THESE MATERIALS AND YOUR DUTY NOT TO MAKE ANY UNAUTHORIZED USE OR DISCLOSURE OF THESE MATERIALS.



NO.	REVISION	DATE	DR.	CK.
	FINISH			
	PLAIN/CLEAN			
	BURR BENCH			
	BLACKOXIDE			
	HEAT TREAT			
	SAND BLAST			
	BUFF			
	PAINT			
	CLEAR CHROMATE			
	OIL			

QTY.	ITEM	DESCRIPTION	PART NO.
REQD.	NO.		STOCK SIZE
ATLANTA ATTACHMENT COMPANY			
NAME SAFE PAUSE & ESTOP SCHEMATIC			
2nd DES. 1306F			
MATERIAL			
NEXT ASSY			PART NO. 1306F-WD3
DES. BY B.PRICE		DRAWING NO.	
DR. BY MATT DASHER		125161E	
CK. BY MATT DASHER		REV 0	
SCALE 1/4		DATE: 11/8/2023 DWG SIZE B	